

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

EXTERIOR LATEX WOOD FINISH SOLID COVER 19 Series

DESCRIPTION: A superior quality solid cover stain that gives new or weathered siding a uniform color while allowing the natural texture of the wood to show through. Provides protection in one or two easy-to-apply coats. Formulated for excellent color retention and moisture resistance.

SUGGESTED USES: On exterior new or weathered wood: fences, siding, shingles, shakes, rough-sawn lumber and lawn furniture.

COLORS: Available in tint bases to provide a range of colors from pastels to deep tones.

FINISH: Flat

GLOSS: $\leq 5^\circ/60^\circ$

VEHICLE TYPE: Vinyl Copolymer

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.2 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 1-2 hours
To Recoat: 8 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 10.4 lbs.

VISCOSITY: 100 KU (± 2 KU)

SOLIDS CONTENT:

By Weight: 44% (± 1)
By Volume: 29% (± 1)

FLASH POINT: Water-based, Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic brush, such as Purdy
Nylox-Swan or Wooster Ultra Pro.
Roll - Synthetic such as Kodawool or Pro Doo-Z
Spray - Graco or Titan Airless - tip size .017 - .019

THINNING INSTRUCTIONS: Thinning not normally required. If necessary, thin with water, no more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Check adhesion to suspected alkyd or oil paints in an area prior to applying latex coatings. If an adhesion problem is present, use the proper primer as an intermediate coat. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

RECOMMENDED BENNETTE PRIMERS:

<i>Cedar/Redwood</i> Acrylic Stain Primer	80230
<i>Wood</i> Exterior Acrylic Latex Primer	70225
Exterior Acrylic Latex Primer	90225
Self Prime (two coat system)	

FORMULATED WITHOUT LEAD OR MERCURY

102401



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.