

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

PORCH & FLOOR ENAMEL 22 series

DESCRIPTION: An alkyd resin enamel designed for use on wood and concrete floors. Formulated for excellent abrasion resistance, flexibility, and hiding power. Dries fast to a smooth, high gloss film that protects and beautifies hardwood and concrete floors.

SUGGESTED USES: Interior/exterior wood and concrete floors. Can also be used as an all purpose enamel for wood trim, doors, and ferrous metal.

COLORS: Five standard colors

FINISH: High Gloss

GLOSS: 75-80°/60°

VEHICLE TYPE: Long/Medium Oil/Alkyd Blend

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.7 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 2-4 hours
To Recoat: 8 hours

MIN/MAX TEMP @ APPLICATION:

40°F min / 95°F max

WEIGHT PER GALLON: 8.9 lbs.

VISCOSITY: 75 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 51% (±1)
By Volume: 42% (±1)

FLASH POINT: Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality natural bristle, such as Purdy Sprig or Wooster Yachtsman.

Roll - Synthetic such as Kodawool or Pro Doo-Z, 1/4" nap

Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning not normally required. If necessary, use Bennette Paint Thinner (330010), up to 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with Bennette Thinner (330010).

SURFACE PREPARATION:

Wood Floors - Self prime with 1 coat thinned 25% with Bennette Mineral Spirits (330010). Follow with second coat at full strength.

Concrete Floors - Etch new concrete with muriatic acid, flush and allow to dry completely. Proceed as with "wood floors" section above.

RECOMMENDED BENNETTE PRIMERS:

<i>Ferrous Metal</i>	Rust Inhib. Metal Primer Yellow	280237
	Rust Inhib. Metal Primer White	280227
	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Galvanized</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227

FORMULATED WITHOUT LEAD OR MERCURY

102401



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.