

# BENNETTE

PAINT MFG. CO., INC.  
PRODUCT DATA

## EXTERIOR OIL WOOD FINISH SOLID COVER 26 Series

**DESCRIPTION:** A quality solid cover wood finish, formulated with premium oils and resins that preserve and beautify exterior rough and smooth wood. This solid cover finish is high-hiding, has good color retention, and dries to a rich, flat finish that allows the wood grain to show through. By penetrating deeply into the wood it seals and protects the wood fibers, providing durability, resistance to moisture, and minimizing warping and cracking.

**SUGGESTED USES:** On exterior new or weathered wood: fences, siding, shingles, shakes, rough-sawn lumber and lawn furniture.

**COLORS:** Available in tint bases to provide a range of colors from pastels to deep tones.

**FINISH:** Flat

**GLOSS:**  $\leq 5^{\circ}/60^{\circ}$

**VEHICLE TYPE:** Long Oil/Alkyd

**RECOMMENDED COVERAGE RATES:**

Approximately 400 sq. ft. per gallon @:  
4.0 mils wet film thickness  
1.7 mils dry film thickness

**DRY TIME (@ 77°F and 50% rel. humidity):**

To Touch: 2 hours  
To Recoat: 24 hours

**MIN/MAX TEMP @ APPLICATION:**

40°F min / 95°F max

**WEIGHT PER GALLON:** 10.1 lbs.

**VISCOSITY:** 80-85 KU ( $\pm 2$  KU)

**SOLIDS CONTENT:**

By Weight: 61% ( $\pm 1$ )  
By Volume: 42% ( $\pm 1$ )

**FLASH POINT:** Combustible

**RECOMMENDED APPLICATION EQUIPMENT:**

Brush - Natural bristle, such as Purdy Sprig or Wooster Friendly

Roll - Lambswool or synthetic, such as Kodawool or Pro Weave

Spray - Graco or Titan Airless - tip size .011- .015

**THINNING INSTRUCTIONS:** Thinning not normally required. If necessary, use Bennette Paint Thinner (330010), up to 1/2 pint per gallon.

**CLEAN UP:** Clean brushes, rollers, and spray equipment immediately after use with Bennette Paint Thinner (330010).

**SURFACE PREPARATION:** Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

**RECOMMENDED BENNETTE PRIMERS:**

<i>Cedar/Redwood Acrylic Stain Primer</i>	80230
<i>Wood Exterior House Paint Primer</i>	270225
Self Prime (two coat system)	

**FORMULATED WITHOUT LEAD OR MERCURY**

102401



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.