

# BENNETTE

PAINT MFG. CO., INC.  
PRODUCT DATA

**PRO'S CHOICE  
ALKYD SEMI-GLOSS  
ENAMEL  
280263**

**DESCRIPTION:** An easy to apply interior alkyd enamel that dries to a smooth, uniform finish that protects and decorates. Ideal for areas of hard usage and high sanitary requirements, it has good resistance to soap and water. The semi-gloss finish is both durable and attractive.

**SUGGESTED USES:** Interior walls, doors, windows and trim in: Homes, offices, classrooms, hospitals, factories, interior drywall, plaster, CMU, and cement block. Especially suited for kitchens and bathrooms. Ideal for wood cabinets.

**COLORS:** White tint base provides a wide range of pastel colors. Custom colors are readily available.

**FINISH:** Semi-Gloss

**GLOSS:** 45-50°/60°

**VEHICLE TYPE:** Alkyd

**RECOMMENDED COVERAGE RATES:**

Approximately 400 sq. ft. per gallon @:  
4.0 mils wet film thickness  
2.1 mils dry film thickness

**DRY TIME (@ 77°F and 50% rel. humidity):**

To Touch: 2 hours  
To Recoat: 24 hours

**MIN/MAX TEMP @ APPLICATION:**

40°F min / 95°F max

**WEIGHT PER GALLON:** 11.0 lbs.

**VISCOSITY:** 90 KU (±2 KU)

**SOLIDS CONTENT:**

By Weight: 74% (±1)  
By Volume: 54% (±1)

**FLASH POINT:** Combustible

**RECOMMENDED APPLICATION EQUIPMENT:**

Brush - Quality natural bristle, such as Purdy Sprig or Wooster Yachtsman.

Roll - Synthetic such as Kodawool or Pro Doo-Z, 1/4" to 3/8" nap

Spray - Graco or Titan Airless - tip size .015 - .017

**THINNING INSTRUCTIONS:** Thinning is not normally required. If necessary, use Bennette Paint Thinner (330010), up to 1/2 pint per gallon for brush and roller, up to 1 pint per gallon for spraying.

**CLEAN UP:** Clean brushes, rollers, and spray equipment immediately after use with Bennette Thinner (330010).

**SURFACE PREPARATION:** Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Previously painted surfaces in good condition may be cleaned and spot-primed with the appropriate primer. Do not apply to any damp or wet surfaces. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

**RECOMMENDED BENNETTE PRIMERS:**

<i>Block, CMU</i>	Acrylic Blockfiller	80250
<i>Concrete</i>	Vinyl Primer Sealer	80225
<i>Drywall</i>	Vinyl Primer Sealer	80225
	Acrylic High Build Wall Primer	80235
<i>Ferrous Metal</i>	Rust Inhib. Metal Primer, Ylw	280237
	Rust Inhib. Metal Primer, White	280227
	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Galvanized</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Plaster</i>	Enamel Undercoater	280233
<i>Wood</i>	Enamel Undercoater	280233
<i>Cedar/Redwood</i>	Acrylic Stain Primer	80230

*Other primers may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.*

**FORMULATED WITHOUT LEAD OR MERCURY**  
102301



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.