

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

**BRONZETONE
ENAMEL
280846**

DESCRIPTION: A versatile interior/exterior enamel designed to protect and decorate a wide variety of substrates. Dries fast to a smooth, durable finish that is resistant to fading, cracking and peeling. Exhibits excellent gloss and color retention. Formulated with anti-corrosive pigments for maximum protection of ferrous metal surfaces.

SUGGESTED USES: Properly primed structural steel, equipment, tanks, wood trim, doors, cabinets, furniture and masonry surfaces.

COLORS: Bronzestone

FINISH: Semi-Gloss

GLOSS: 55-65°/60°

VEHICLE TYPE: Medium Oil/Alkyd

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.4 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 2-4 hours
To Recoat: 8 hours

MIN/MAX TEMP @ APPLICATION:

40°F min / 95°F max

WEIGHT PER GALLON: 8.9 lbs.

VISCOSITY: 85 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 51% (±1)
By Volume: 34% (±1)

FLASH POINT: Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality natural bristle, such as Purdy Sprig or Wooster Yachtsman.
Roll - Synthetic such as Kodawool or Pro Doo-Z, 1/4" nap
Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning is not normally required. If necessary, use Bennette Paint Thinner (330010), up to 1/2 pint per gallon. For spray application, thin with Bennette VM&P Naphtha (330002) up to 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with Bennette Thinner (330010).

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

RECOMMENDED BENNETTE PRIMERS:

<i>Block, CMU</i>	Acrylic Blockfiller	80250
<i>Ferrous Metal</i>	Rust Inhib. Metal Primer Yellow	280237
	Rust Inhib. Metal Primer White	280227
	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Galvanized</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227

INTERIOR

<i>Drywall</i>	Enamel Undercoater	280233
<i>Plaster</i>	Enamel Undercoater	280233
<i>New Wood</i>	Enamel Undercoater	280233

EXTERIOR

<i>New Wood</i>	Exterior House Paint Primer	270225
-----------------	-----------------------------	--------

FORMULATED WITHOUT LEAD OR MERCURY

102401



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.