

# BENNETTE

PAINT MFG. CO., INC.  
PRODUCT DATA

## LATEX STUCCO AND MASONRY TEXTURED COATING 32-42 MPI #42

**DESCRIPTION:** A heavy-bodied fibered coating that decorates and protects. Combines the aesthetic qualities of a medium texture finish with the durability of a top quality vinyl resin system. Exhibits excellent resistance to moisture and mildew, remains flexible, and hides minor surface imperfections.

**SUGGESTED USES:** Exterior (and interior) filled or primed masonry surfaces where a textured finish is desired. Can also be used on properly primed interior drywall and wood.

**COLORS:** White. May be tinted to a wide range of pastel colors. Custom colors are readily available.

**FINISH:** Flat, medium texture

**GLOSS:**  $\leq 5^\circ/85^\circ$

**VEHICLE TYPE:** Vinyl Copolymer

**RECOMMENDED COVERAGE RATES:**

Approximately 60-75 ft. per gallon @:  
10-12 mils wet film thickness  
6-8 mils dry film thickness

**DRY TIME (@ 77°F and 50% rel. humidity):**

To Touch: 2-4 hours  
To Recoat: 48 hours

**MIN/MAX TEMP @ APPLICATION:**

50°F min / 95°F max

**WEIGHT PER GALLON:** 10.4 lbs.

**VISCOSITY:** 125 KU ( $\pm 2$  KU)

**SOLIDS CONTENT:**

By Weight: 63% ( $\pm 1$ )  
By Volume: 59% ( $\pm 1$ )

**FLASH POINT:** Water-based, Combustible

**RECOMMENDED APPLICATION EQUIPMENT:**

Brush - Quality synthetic brush, such as Purdy Nylox-Swan or Wooster Ultra Pro.  
Roll - Texture Roller  
Spray - Texture machine & hopper gun or auger-driven texture pump

**THINNING INSTRUCTIONS:** Thinning is not normally required. If necessary, thin with water, no more than 1 pint per gallon.

**CLEAN UP:** Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

**SURFACE PREPARATION:** Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Check adhesion to suspected alkyd or oil paints in an area prior to applying latex coatings. If an adhesion problem is present, use the proper primer as an intermediate coat. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

**RECOMMENDED BENNETTE PRIMERS:**

**INTERIOR**

Drywall	Interior Latex Primer Sealer	32-50
Wood	Interior Latex Primer Sealer	32-50

**INTERIOR/EXTERIOR**

Block, CMU	Int/Ext Latex Blockfiller	32-4
Wood	Exterior Latex Wood Primer	32-6
Concrete	Exterior Latex Wood Primer	32-6
Brick	Exterior Latex Wood Primer	32-6

*Other primers may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.*

This product was formulated with no mercury compounds, asbestos, silica sand, lead chromate, or insecticide and not more than 0.06 percent lead.

012203



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.