

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

SIGNATURE
INTERIOR ACRYLIC
EGGSHELL ENAMEL
4 Series

DESCRIPTION: A premium quality acrylic paint that combines excellent durability with ease of application. Provides a rich, durable, low luster finish that makes it easy to clean away typical household marks without damaging the paint film. Other characteristics include spatter resistance, excellent leveling, and one coat hiding in most cases. All *Signature* series paints are specifically formulated for those customers who desire the very finest quality available.

SUGGESTED USES: Interior walls, doors, windows, and trim. Ideally suited for bathrooms and kitchens.

COLORS: White and tint bases provide a range of colors from pastel to deeptone, and custom colors are readily available.

FINISH: Eggshell

GLOSS: 15-20°/60°

VEHICLE TYPE: Acrylic

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:

4.0 mils wet film thickness

1.5 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 30 minutes to 1 hour

To Recoat: 8 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 10.8 lbs.

VISCOSITY: 95-100 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 46% (±1)

By Volume: 30% (±1)

FLASH POINT: Water-based, Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic Bristle, such as Purdy
Nylox-Swan or Wooster Ultra Pro

Roll - Synthetic Superfab 1/4" to 3/8" nap

Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning is not normally required. If necessary, thin with water, no more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Previously painted surfaces in good condition may be cleaned and spot-primed with the appropriate primer. Do not apply to any damp or wet surfaces. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

RECOMMENDED BENNETTE PRIMERS:

<i>Block, CMU</i>	Acrylic Blockfiller	80250
<i>Concrete</i>	Vinyl Primer Sealer	80225
<i>Drywall</i>	Vinyl Primer Sealer	80225
	Acrylic High Build Wall Primer	80235
<i>Ferrous Metal</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
	Rust Inhib. Metal Primer, Ylw	280237
	Rust Inhib. Metal Primer, White	280227
<i>Galvanized</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Plaster</i>	Enamel Undercoater	280233
<i>Wood</i>	Vinyl Primer Sealer	80225
<i>Cedar/Redwood</i>	Acrylic Stain Primer	80230

Other primers may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.

FORMULATED WITHOUT LEAD OR MERCURY
102301



EMPLOYEE
OWNED
COMPANY

All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.