

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

**PRO'S CHOICE
ACRYLIC
SEMI-GLOSS
5 Series**

DESCRIPTION: An excellent quality interior acrylic latex semi-gloss enamel formulated to be durable and economical. Combines the benefits of a high quality resin system with excellent hide and leveling. Pro's Choice is the product of choice for areas requiring an economical low-odor, fast-drying, washable semi-gloss finish.

SUGGESTED USES: Interior walls, doors, windows, and trim in: Homes, offices, classrooms, hospitals, factories, interior drywall, plaster, CMU, and cement block. Especially suited for kitchens and bathrooms.

COLORS: Super White and Shell White. Pastel and medium tint bases provide a wide color range. Custom colors are readily available.

FINISH: Semi-Gloss

GLOSS: 50-60°/60°

VEHICLE TYPE: Vinyl Acrylic Copolymer

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.1 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 2 hours
To Recoat: 8 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 10.1 lbs.

VISCOSITY: 95 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 40% (±1)
By Volume: 27% (±1)

FLASH POINT: Water-based, Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic Bristle, such as Purdy Nylox-Swan or Wooster Ultra Pro
Roll - Synthetic Superfab 1/4" to 3/8" nap
Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning is not normally required. If necessary, thin with water, no more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Check adhesion to suspected alkyd or oil paints in an area prior to applying latex coatings. If an adhesion problem is present, use the proper primer as an intermediate coat. New or unpainted surfaces should be primed in accordance with the "Recommended Bennette Primers" section of this sheet.

RECOMMENDED BENNETTE PRIMERS:

<i>Block, CMU</i>	Acrylic Blockfiller	80250
<i>Concrete</i>	Vinyl Primer Sealer	80225
<i>Drywall</i>	Vinyl Primer Sealer	80225
	Acrylic High Build Wall Primer	80235
<i>Ferrous Metal</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
	Rust Inhib. Metal Primer, Ylw	280237
	Rust Inhib. Metal Primer, White	280227
<i>Galvanized</i>	Acrylic Metal Primer, Red	80228
	Acrylic Metal Primer, White	80227
<i>Plaster</i>	Enamel Undercoater	280233
<i>Wood</i>	Vinyl Primer Sealer	80225
<i>Cedar/Redwood</i>	Acrylic Stain Primer	80230

Other primers may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.

FORMULATED WITHOUT LEAD OR MERCURY

020604



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.