

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

EXTERIOR ACRYLIC HOUSE PAINT PRIMER 70225

DESCRIPTION: An exterior primer which combines excellent adhesion and sealing properties with fast dry time and easy application. Formulated to develop a "breathing" system when topcoated with any quality Bennette Exterior Latex Finish.

SUGGESTED USES: Properly prepared exterior wood siding, trim, windows, and doors, vinyl and aluminum siding, and non-porous masonry surfaces.

COLORS: White, may be tinted to pastel colors to approximate color of finish coat.

FINISH: Low Sheen

GLOSS: $\leq 5^\circ/60^\circ$

VEHICLE TYPE: 100% Acrylic

PIGMENT TYPE: Titanium Dioxide, Silicates, Zinc, and Mica

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.4 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 30 minutes - 1 hour
To Recoat: 2 - 4 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 11.0 lbs.

VISCOSITY: 85-90 KU (± 2 KU)

SOLIDS CONTENT:

By Weight: 52% (± 1)
By Volume: 36% (± 1)

FLASH POINT: Water-based, Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic brush, such as Purdy Nylox-Swan or Wooster Ultra Pro.
Roll - Synthetic such as Kodawool 1/2" to 3/4" nap
Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning is not normally required. If necessary, thin with water, not more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Check adhesion to suspected alkyd or oil paints in an area prior to applying latex coatings. If an adhesion problem is present, use the proper primer as an intermediate coat.

RECOMMENDED BENNETTE FINISHES:

<i>Flat</i>	Signature Exterior Acrylic Flat	21 series
	Exterior Latex Flat House Paint	9 series
	Exterior Acrylic Flat	11 series
	Exterior Latex Wood Finish	19 series
<i>Satin</i>	Signature Acrylic Satin Enamel	36 series
<i>Semi-Gloss</i>	Signature Acrylic Semi-Gloss	37 series
	Exterior Acrylic Semi-Gloss	7 series
	Exterior Acrylic Semi-Gloss	13 series
<i>Gloss</i>	Signature Exterior Acrylic Gloss	20 series

Other finishes may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.

NOTE: Not recommended for cedar or redwood - use Bennette 80230 instead.

FORMULATED WITHOUT LEAD OR MERCURY

102301



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.