

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

WHITE ACRYLIC TRAFFIC PAINT 80215

DESCRIPTION: A non-chrome, waterborne striping paint, specifically formulated for use on traffic bearing surfaces. This product exhibits quality performance while possessing the environmental advantages of a waterborne system.

SUGGESTED USES: Streets, parking lots, any lane marking areas. Interior/exterior cement and asphalt surfaces. Can be used in conjunction with glass beads. Aggregate or non-skid should be added for use on ramps or inclines.

COLOR: White. May be tinted to pastel colors, including Handicap Blue.

FINISH: Flat

GLOSS: 1°/85°

VEHICLE TYPE: Acrylic

RECOMMENDED COVERAGE RATES:

Approximately 300 linear feet per gallon @:
10 mils wet film thickness
5 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

Dependent upon mils applied.
To Touch: 15-30 minutes
To Recoat: 2-4 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 12.8 lbs.

VISCOSITY: 95-100 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 64% (±1)
By Volume: 44% (±1)

FLASH POINT: Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic brush, such as Purdy
Nylox-Swan or Wooster Ultra Pro.

Roll - Synthetic such as Kodawool or Superfab

Spray - Graco or Titan Airless Striping Machine -
tip size .015 - .019

THINNING INSTRUCTIONS: Thinning is not recommended because it will reduce solids and durability.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Heavy grease and oil should be removed to promote adhesion. Broom sweep loose dirt and dust. Do not apply when chance of precipitation is evident, to insure total uninterrupted proper cure. Apply to dry substrate.

NOTE: Should not be applied if air temperature is expected to fall below 50°F or if moisture or precipitation could be in contact with fresh paint within 24 hours after application.

FORMULATED WITHOUT LEAD OR MERCURY

102401



EMPLOYEE
OWNED
COMPANY

All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.