

# BENNETTE

PAINT MFG. CO., INC.  
PRODUCT DATA

## INTERIOR VINYL PRIMER SEALER 80225

**DESCRIPTION:** A unique acrylic primer designed for use on new drywall. When applied properly, this primer minimizes surface porosities and imperfections, resulting in a smooth, uniform surface which can be easily topcoated with any Bennette interior finish. Also exhibits excellent enamel holdout when used as a prime coat on new wood and wood trim.

**SUGGESTED USES:** Interior drywall and wood trim.

**COLORS:** White, may be tinted to pastel colors to approximate color of finish coat.

**FINISH:** Flat

**GLOSS:**  $\leq 5^\circ/85^\circ$

**VEHICLE TYPE:** Acrylic

**PIGMENT TYPE:** Titanium Dioxide, Silicates, and Carbonates

**THEORETICAL COVERAGE RATES:**

Approximately 350 sq. ft. per gallon @:  
4.6 mils wet film thickness  
1.4 mils dry film thickness

**DRY TIME (@ 77°F and 50% rel. humidity):**

To Touch: 30 minutes  
To Recoat: 2 hours

**MIN/MAX TEMP @ APPLICATION:**

50°F min / 95°F max

**WEIGHT PER GALLON:** 11.7 lbs.

**VISCOSITY:** 100-105 KU ( $\pm 2$  KU)

**SOLIDS CONTENT:**

By Weight: 48% ( $\pm 1$ )  
By Volume: 30% ( $\pm 1$ )

**V.O.C.:** 50 g/L (0.41 lb/gal) [LEED N.C 2.2 <150 g/L]

**FLASH POINT:** Water-based, Combustible

**RECOMMENDED APPLICATION EQUIPMENT:**

Brush - Quality synthetic brush, such as Purdy Nylox-Swan or Wooster Ultra Pro.  
Roll - Synthetic such as Kodawool 3/8" to 3/4" nap  
Spray - Graco or Titan Airless - tip size .017 - .019

**NOTE:** Higher viscosity is designed for optimum performance when spray applied.

**THINNING INSTRUCTIONS:** Thinning reduces sealing characteristics and is not recommended.

**CLEAN UP:** Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

**SURFACE PREPARATION:** Surface must be free of dirt, chalk, wax or other foreign substances.

Use on new, bare drywall construction: Joint compound must be thoroughly dry and sanded smooth. Repair any significant surface damage, cracks, holes, etc. Remove all sanding dust and construction dust by sweeping or vacuuming. Seal stains from water, ink, pencil, grease, etc., with Bennette Acrylic Stain Primer (80230)

**RECOMMENDED BENNETTE FINISHES:**

<i>Flat</i>	Signature Latex Interior Flat	1 series
	Designer Acrylic Flat	18 series
	Pro's Choice Vinyl Flat	2 series
<i>Eggshell</i>	PC Interior Acrylic Flat	12 series
	Pro's Choice Acrylic Flat	10 series
	Production Flat Latex	8 series
<i>Satin</i>	Signature Acrylic Eggshell Enml	4 series
	Pro's Choice Acrylic Eggshell	80995
<i>Semi-Gloss</i>	Signature Acrylic Satin Enamel	38 series
	Signature Acrylic Semi-Gloss	24 series
	Premium Plus Latex Semi-Gloss	3 series
	Pro's Choice Acrylic Semi-Gloss	5 series
<i>Gloss</i>	Bennette Acrylic Semi-Gloss	16 series
	Signature Acrylic Gloss	20 series

*Other finishes may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.*

**FORMULATED WITHOUT LEAD OR MERCURY**  
102301



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.