

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

LATEX SUPER KILL PRIMER-SEALER 80226

DESCRIPTION: An interior, fast-dry, acrylic primer that will seal light smoke, water stains, and many household stains without the strong solvent odor associated with oil-based sealers.

SUGGESTED USES: Seals light smoke, water, and many other stain damage on drywall, plaster, and wood. Severe stains, including, but not limited to, smoke, soot, and nicotine may require cleaning prior to painting. For severe stains, two coats of 80226 are recommended or use Bennette 80230 Acrylic Stain Primer.

COLORS: White

FINISH: Low Sheen

GLOSS: 10-20°/60°

VEHICLE TYPE: 100% Acrylic

PIGMENT TYPE: Titanium Dioxide, Carbonates, Zinc Compounds

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.4 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 1 hour
To Recoat: 2 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 11 lbs.

VISCOSITY: 100-105 KU (±2 KU)

SOLIDS CONTENT:

By Weight: 52% (±1)
By Volume: 35% (±1)

FLASH POINT: Water-based, Combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic brush, such as Purdy Nylox-Swan or Wooster Ultra Pro.
Roll - Synthetic such as Pro-Doo-Z 1/4" - 3/8" nap
Spray - Graco or Titan Airless - tip size .013 - .015

THINNING INSTRUCTIONS: Thinning not normally required. If necessary, thin with water, no more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores.

RECOMMENDED BENNETTE FINISHES:

<i>Flat</i>	Signature Latex Interior Flat	1 series
	Designer Acrylic Flat	18 series
	Pro's Choice Acrylic Flat	10 series
<i>Eggshell</i>	Signature Acrylic Eggshell Enml	4 series
	Pro's Choice Acrylic Eggshell	80995
<i>Satin</i>	Signature Acrylic Satin Enamel	38 series
	Value Plus Latex Satin Enamel	15 series
<i>Semi-Gloss</i>	Signature Acrylic Semi-Gloss	24 series
	Premium Plus Latex Semi-Gloss	3 series
	Pro's Choice Acrylic Semi-Gloss	5 series
	Bennette Acrylic Semi-Gloss	16 series
<i>Gloss</i>	Signature Acrylic Gloss	20 series

Other finishes may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.

NOTE: For adhesion to questionable surfaces, test patches should be utilized prior to topcoating. This primer is not recommended for cedar or redwood.

FORMULATED WITHOUT LEAD OR MERCURY
102301



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.