

BENNETTE

PAINT MFG. CO., INC.
PRODUCT DATA

EXTERIOR ACRYLIC LATEX PRIMER 90225

DESCRIPTION: An exterior primer specifically designed for most types of wood when performance and cost are most important. Formulated to provide good sealing characteristics when properly applied, allowing good results when using any Bennette exterior latex finish.

SUGGESTED USES: Exterior wood and blockfilled, non-porous masonry surfaces.

COLORS: White, may be tinted to pastel colors to approximate color of finish coat.

FINISH: Low Sheen

GLOSS: $\leq 5^{\circ}/60^{\circ}$

VEHICLE TYPE: Acrylic blend

PIGMENT TYPE: Titanium Dioxide, Silicates

RECOMMENDED COVERAGE RATES:

Approximately 400 sq. ft. per gallon @:
4.0 mils wet film thickness
1.5 mils dry film thickness

DRY TIME (@ 77°F and 50% rel. humidity):

To Touch: 30 minutes - 1 hour
To Recoat: 2 - 4 hours

MIN/MAX TEMP @ APPLICATION:

50°F min / 95°F max

WEIGHT PER GALLON: 10.8 lbs.

VISCOSITY: 95-100 KU (± 2 KU)

SOLIDS CONTENT:

By Weight: 50% (± 1)
By Volume: 34% (± 1)

FLASH POINT: Water-based, combustible

RECOMMENDED APPLICATION EQUIPMENT:

Brush - Quality synthetic brush, such as Purdy
Nylox-Swan or Wooster Ultra Pro.
Roll - Synthetic such as Kodawool 1/2" to 3/4" nap
Spray - Graco or Titan Airless - tip size .015 - .017

THINNING INSTRUCTIONS: Thinning is not normally required. If necessary, thin with water, not more than 1/2 pint per gallon.

CLEAN UP: Clean brushes, rollers, and spray equipment immediately after use with warm, soapy water.

SURFACE PREPARATION: Surface must be free of dirt, chalk, wax or other foreign substances. Glossy surfaces should be sanded and/or scrubbed with a de-glossing solution. Remove mildew with a solution that kills mildew spores. Not recommended for applying to existing alkyd or oil paints. Check adhesion to insure positive results. Topcoat within 72 hours of priming to insure good subsequent adhesion. In problem areas, additional mildewcide is recommended.

RECOMMENDED BENNETTE FINISHES:

<i>Flat</i>	Signature Exterior Acrylic Flat	21 series
	Exterior Latex Flat House Paint	9 series
	Exterior Acrylic Flat	11 series
	Exterior Latex Wood Finish	19 series
<i>Satin</i>	Signature Acrylic Satin Enamel	36 series
<i>Semi-Gloss</i>	Signature Acrylic Semi-Gloss	37 series
	Exterior Acrylic Semi-Gloss	7 series
	Exterior Acrylic Semi-Gloss	13 series
<i>Gloss</i>	Signature Acrylic Gloss	20 series

Other finishes may be acceptable. Contact Bennette Paint Mfg. Co., Inc. for more information.

NOTE: Not recommended for cedar or redwood - use Bennette 80230 instead. Also, will not hold back rust on non-galvanized nail heads - use Bennette 70225 instead.

FORMULATED WITHOUT LEAD OR MERCURY
102301



All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data that the Seller believes to be reliable, and are intended for use by persons having skill and know-how at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.