

SECTION 1 - Product and Company Identification		INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
Manufacturer:	E.I. du Pont de Nemours & Co. Du Pont Performance Coatings Wilmington, DE, 19898	Ethylbenzene	100-41-4	7.0	A 125.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 25.0 ppm 8 & 12 hour TWA
Telephone:	Product information: (800) 441-7515 Medical emergency: (800) 441-3637 Transportation emergency: (800) 424-9300 (CHEMTREC)	Hydrous magnesium silicate	14807-96-6	None	A 2.0 mg/m3 Respirable Dust D 0.5 mg/m3 8 & 12 hour TWA Respirable Dust O None
Product:	<b>Tufcote®Alkyd and Corlar®Epoxy Colorants</b>	Iron oxide	1309-37-1	None	A 5.0 mg/m3 O 10.0 mg/m3
DOT Shipping Name:	See DOT addendum.	Limestone (calcium carbonate)	1317-65-3	None	A 10.0 mg/m3 O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust
Hazardous Materials Information:	See Section 10.	Manganese (iv) oxide	1313-13-9	None	A 0.2 mg/m3 Mn O 5.0 mg/m3 CEIL Mn
SECTION 2 - Composition/information on ingredients					
INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS		
1,2,4-trimethyl benzene	95-63-6	7.0@44.4°C	A 25.0 ppm O 25.0 ppm		
Aldehyde resin	NotAvail	2.0	A None O None		
Alkyd resin	150739-98-3	None	A None O None	Methyl ethyl ketone	78-93-3 89.0 @ 0.0
Amorphous silica	7631-86-9	2.0	A 10.0 mg/m3 Total Dust O 20.0 mppcf D 3.0 mg/m3		A 300.0ppm 15 min STEL A 200.0 ppm O 200.0 ppm D 300.0 ppm 15 min TWA D 200.0 ppm 8 & 12 hour TWA
Aromatic hydrocarbon	64742-95-6	10.0@25.0°C	D 50.0 ppm A None O None	Phthalocyanine blue pigment	147-14-8 None
Azo yellow pigment	31837-42-0	None	A 10.0 mg/m3 O 5.0 mg/m3 Respirable Dust O 15.0 mg/m3		A 10.0 mg/m3 inhalable dust PNOC A 3.0 mg/m3 respirable particulate PNOC O 15.0 mg/m3 Total Dust PNOR O 5.0 mg/m3 TWA Respirable Dust PNOR
Barium sulfate	7727-43-7	None	A 10.0 mg/m3 Total Dust A 5.0 mg/m3 Respirable Dust O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust D 10.0 mg/m3 Total Dust	Phthalocyanine green pigment	14302-13-7 None
Carbon black	1333-86-4	None	A 3.5 mg/m3 O 3.5 mg/m3 D 0.5 mg/m3 8 & 12 hour TWA	Proprietary pigment 1	NotAvail None
				Proprietary pigment 2	NotAvail None
Dipropylene glycol methyl ether	34590-94-8	0.4@25.0°C	A 150.0 ppm 15 min STEL Skin A 100.0 ppm Skin O 100.0 ppm Skin	Proprietary pigment 3	NotAvail None
				Proprietary pigment 4	NotAvail None

INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS	INGREDIENTS	CAS #	VAPOR PRESSURE	EXPOSURE LIMITS
Proprietary resin 1	Not Avail	None	A None O None	Yellow pigment	20344-49-4	None	O 5.0 mg/m3 PEL Total Dust O 15.0 mg/m3 PEL PNOR A None
Proprietary resin 2	Not Avail	None	A None O None				
Propylene glycol monomethyl ether acetate	108-65-6	3.8	D 10.0 ppm 8 & 12 hour TWA A None O None				
Quartz-crystalline silica	14808-60-7	<0.0	A 50.0 ug/m3 Respirable Dust O 0.1 mg/m3 Respirable Dust D 0.1 mg/m3 Respirable Dust				
Quinacridone pigment	1047-16-1	None	A 10.0 mg/m3 inhalable dust A 3.0 mg/m3 O 15.0 mg/m3 Total Dust PNOR O 5.0 mg/m3 Respirable Dust D 10.0 mg/m3 Total Dust				
Red iron oxide light	1332-37-2	None	A 10.0 mg/m3 PNOR A 3.0 mg/m3 Respirable Dust A 5.0 mg/m3 Fe O 15.0 mg/m3 Total Dust O 5.0 mg/m3 Respirable Dust				
Titanium dioxide	13463-67-7	None	A 10.0 mg/m3 O 15.0 mg/m3 Total Dust D 10.0 mg/m3 Total Dust D 5.0 mg/m3 Respirable Dust				
Toluene	108-88-3	22.0	A 50.0 ppm Skin O 300.0 ppm CEIL O 500.0 ppm 10 min TWA O 200.0 ppm D 50.0 ppm 8 & 12 hour TWA				
Xylene	1330-20-7	8.0@25.0°C	A 150.0 ppm 15 min STEL A 100.0 ppm O 100.0 ppm D 150.0 ppm 15 min STEL D 100.0 ppm 8 & 12 hour TWA				

\*A=ACGIH, O=OSHA, D=DuPont, S=Suppliers. Limits are 8 hour TWA unless otherwise specified. Vapor pressure @20°C unless otherwise noted.

**SECTION 3 - Hazards identification**

**Potential Health Effects:**

**Inhalation:**

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**Ingestion:**

May result in gastrointestinal distress

**Skin or Eye Contact:**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

**Other Potential Health Effects in addition to those listed above:**

**Aromatic hydrocarbon**

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

**Carbon black**

Is an IARC, NTP or OSHA carcinogen. Has shown carcinogenic activity in laboratory animals at high doses. Significance to man is unknown. The following medical conditions may be aggravated by exposure: asthma, respiratory disease.  
WARNING: This chemical is known to the State of California to cause cancer.

**Ethylbenzene**

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects.  
WARNING: This chemical is known to the State of California to cause cancer.

**Iron oxide**

Ingestion may cause: any of the following: gastric disturbances. Skin or eye contact may cause any of the following: mechanical irritation. Inhalation may cause any of the following: respiratory tract irritation.

**Methyl ethyl ketone**

Material is irritating to mucous membranes and upper respiratory tract. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, eyes, respiratory system, skin. Prolonged or repeated overexposure may cause any of the following: conjunctivitis, dermatitis. High concentrations have caused embryotoxic effects in laboratory animals. Aspiration may occur during swallowing or vomiting, resulting in

lung damage. Ingestion may cause headache, nausea, vomiting, dizziness, and drowsiness.

**Propylene glycol monomethyl ether acetate**

Recurrent overexposure may result in liver and kidney injury.

**Quartz-crystalline silica**

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury.

WARNING: This chemical is known to the State of California to cause cancer.

**Red iron oxide light**

Long-term respiratory exposure of iron oxide may result in deposition of particles in the lung (benign siderosis).

**Titanium dioxide**

In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m<sup>3</sup> respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m<sup>3</sup> level are not relevant to the workplace.

**Toluene**

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. Can be absorbed through the skin in harmful amounts. Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown.

WARNING: This chemical is known to the State of California to cause birth defects or other reproductive harm.

**Xylene**

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

**SECTION 4 - First aid measures**

**First Aid Procedures:**

**Inhalation:**

If affected by inhalation of vapor or spray mist, move to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulty persists, or occurs later, consult a physician.

**Ingestion:**

In the unlikely event of ingestion, DO NOT INDUCE VOMITING. Call a physician immediately and have names of ingredients available.

**Skin or Eye Contact:**

In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash thoroughly with soap and water. If irritation occurs, contact a physician.

**SECTION 5 - Fire-fighting measures**

**Flash Point (Closed Cup):** See Section 11 for exact values

**Flammable Limits:** LFL 0% UFL 12.3%

**Extinguishing Media:**

Universal aqueous film-forming foam, carbon dioxide, dry chemical.

**Fire Fighting Procedures:**

Full protective equipment, including self-contained breathing apparatus, is recommended. Water from fog nozzles may be used to prevent pressure build-up.

**Fire and Explosion Hazards:**

For flammable liquids, vapor/air will ignite when an ignition source is present. In other cases, when heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

**SECTION 6 - Accidental release measures**

**Steps to be taken in case material is released or spilled:**

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

**SECTION 7 - Handling and storage**

**Precautions to be taken in handling and storing:**

Observe label precautions. If combustible (flashpoint between 100-200 .F), keep away from heat, sparks and flame. If flammable (flashpoint less than 100. F), also keep away from static discharges and other sources of ignition. If material is extremely flammable (flashpoint less than 20. F) or flammable, VAPORS MAY IGNITE EXPLOSIVELY OR CAUSE FLASH FIRE, respectively. Vapors may spread long distances. Prevent buildup of vapors. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120 .F. If product is waterbased do not freeze.

**Other precautions:**

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved respirator or appropriate ventilation, and gloves.

**SECTION 8 - Exposure controls / personal protection**

**Engineering controls and work practices:**

**Ventilation:**

Provide sufficient ventilation in volume and pattern to keep contaminants below applicable exposure limits.

**Respiratory protection**

Do not breathe vapors or mists. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A) during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air-purifying respirator fit is not possible, wear a positive pressure, supplied-air respirator (NIOSH TC-19C). In all cases, follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area.

**Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Skin protection**

Neoprene gloves and coveralls are recommended.

**Eye protection**

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

**SECTION 9 - Physical and chemical properties**

Evaporation rate	Slower than Ether
Solubility in Water	NIL
Vapor Density	Heavier than air
Approx. Boiling Range(°C)	No Data available
Approx. Freezing Range(°C)	-86.6 - 34 °C
Gallon weight (lbs/gal)	8.64 - 16.39
Specific Gravity	1.04 - 1.96
Percent Volatile by Volume	38.41 - 60.93
Percent Volatile by Weight	18.50 - 52.40
Percent Solid by Volume	39.07 - 61.59
Percent Solid by Weight	47.60 - 81.50

**SECTION 10 - Stability and reactivity****Stability:**

Stable

**Incompatibility (materials to avoid):**

None reasonably foreseeable

**Hazardous Decomposition Products:**

CO, CO2, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

**Hazardous Polymerization:**

Will not occur.

**Sensitivity to Static Discharge:**

For flammable materials (flashpoint less than 100 deg F) and combustibles (flashpoint between 100-200 deg F) if heated above the flashpoint, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

**Sensitivity to Mechanical Impact:**

None known

**SECTION 11 - Additional Information****Product Code                      Ingredients (Product Specific)**

**250-34761™** 1,2,4-trimethyl benzene(3.3 - 3.3%\*), Alkyd resin(48.0%), Aromatic hydrocarbon(5.2 - 5.2%), Carbon black(0.9%), Ethylbenzene(2.2 - 5.4%\* @), Limestone (calcium carbonate)(6.7%), Methyl ethyl ketone (6.7%), Red iron oxide light (2.0%), Xylene (16.4-19.6%\* @)  
**GAL WT: 8.64 WT PCT SOLIDS: 59.39 VOL PCT SOLIDS: 50.72**  
**SOLVENT DENSITY: 7.09 VOC LE: 3.5 VOC AP: 3.5**  
**FLASH POINT: 20°F to below 73°F H: 2 F: 3 R: 0 OSHA STORAGE: IB**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES**

**4000P(TW)™** Aldehyde resin(16.1%), Amorphous silica(2.2%), Dipropylene glycol methyl ether(16.0%), Ethylbenzene(0.9%\* @), Titanium dioxide(63.2%)  
**GAL WT: 16.21 WT PCT SOLIDS: 81.50 VOL PCT SOLIDS: 61.59**  
**SOLVENT DENSITY: 7.81 VOC LE: 3.0 VOC AP: 3.0**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4009P(OY)™** Aldehyde resin(32.0%), Azo yellow pigment(19.0%), Barium sulfate(15.7%), Dipropylene glycol methyl ether(28.9%), Ethylbenzene(0.5%\* @), Titanium dioxide(3.3%)  
**GAL WT: 10.64 WT PCT SOLIDS: 70.20 VOL PCT SOLIDS: 59.81**  
**SOLVENT DENSITY: 7.89 VOC LE: 3.2 VOC AP: 3.2**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4014P(MY)™** Aldehyde resin(16.1%), Barium sulfate(15.3%), Ethylbenzene(1.0%\* @), Proprietary pigment 3(14.5%), Proprietary pigment 4(14.5%), Proprietary resin 2(1.9%), Propylene glycol monomethyl ether acetate(34.8%), Xylene(1.0%\* @)  
**GAL WT: 11.27 WT PCT SOLIDS: 63.10 VOL PCT SOLIDS: 49.89**  
**SOLVENT DENSITY: 8.65 VOC LE: 4.1 VOC AP: 4.1**  
**FLASH POINT: 100°F - 141°F H: 2 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4023P(PG)™** Aldehyde resin(25.5%), Barium sulfate(22.3%), Dipropylene glycol methyl ether(32.0%), Ethylbenzene(0.1%\* @), Hydrous magnesium silicate(1.4%), Phthalocyanine green pigment(17.8%)  
**GAL WT: 11.52 WT PCT SOLIDS: 67.00 VOL PCT SOLIDS: 51.84**  
**SOLVENT DENSITY: 7.90 VOC LE: 3.8 VOC AP: 3.8**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4034P(PB)™** Aldehyde resin(23.8%), Barium sulfate(1.4%), Dipropylene glycol methyl ether(52.1%), Ethylbenzene(0.1%\* @), Phthalocyanine blue pigment(21.5%)  
**GAL WT: 9.20 WT PCT SOLIDS: 47.60 VOL PCT SOLIDS: 39.07**  
**SOLVENT DENSITY: 7.92 VOC LE: 4.8 VOC AP: 4.8**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4038P(QV)™** Aldehyde resin(28.7%), Barium sulfate(28.2%), Dipropylene glycol methyl ether(28.6%), Ethylbenzene(0.3%\* @), Quinacridone pigment(13.0%)  
**GAL WT: 11.56 WT PCT SOLIDS: 70.90 VOL PCT SOLIDS: 57.39**  
**SOLVENT DENSITY: 7.90 VOC LE: 3.4 VOC AP: 3.4**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4045P(RO)™** Aldehyde resin(17.1%), Dipropylene glycol methyl ether(21.2%), Ethylbenzene(0.1%\* @), Iron oxide(35.5%), Red iron oxide light(24.7%)  
**GAL WT: 16.39 WT PCT SOLIDS: 78.20 VOL PCT SOLIDS: 54.76**  
**SOLVENT DENSITY: 7.89 VOC LE: 3.6 VOC AP: 3.6**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4048P(QR)™** Aldehyde resin(30.0%), Barium sulfate(22.5%), Dipropylene glycol methyl ether(31.0%), Ethylbenzene(0.3%\* @), Hydrous magnesium silicate(1.1%), Quinacridone pigment(14.9%)  
**GAL WT: 10.91 WT PCT SOLIDS: 68.50 VOL PCT SOLIDS: 56.53**  
**SOLVENT DENSITY: 7.92 VOC LE: 3.4 VOC AP: 3.4**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4066P(UO)™** Aldehyde resin(17.0%), Barium sulfate(15.1%), Ethylbenzene(1.0%\* @), Hydrous magnesium silicate(1.9%), Proprietary pigment 1(15.5%), Proprietary pigment 2(15.5%), Proprietary resin 1(2.0%), Propylene glycol monomethyl ether acetate(31.0%)  
**GAL WT: 11.69 WT PCT SOLIDS: 66.90 VOL PCT SOLIDS: 54.29**  
**SOLVENT DENSITY: 9.08 VOC LE: 3.9 VOC AP: 3.9**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4075P(YO)™** Aldehyde resin(21.5%), Barium sulfate(6.7%), Dipropylene glycol methyl ether(24.5%), Ethylbenzene(0.1%\* @), Yellow pigment(47.2%)  
**GAL WT: 14.25 WT PCT SOLIDS: 75.40 VOL PCT SOLIDS: 55.68**  
**SOLVENT DENSITY: 7.91 VOC LE: 3.5 VOC AP: 3.5**  
**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**  
**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4084P(BU)™** Aldehyde resin(25.0%), Barium sulfate(10.0%), Dipropylene glycol methyl ether(24.4%), Ethylbenzene(0.1%\* @), Iron oxide(22.2%), Limestone (calcium carbonate)(6.0%), Manganese (iv) oxide(6.0%\* @), Quartz-crystalline silica(6.1%)  
**GAL WT: 13.23 WT PCT SOLIDS: 75.30 VOL PCT SOLIDS: 58.72**  
**SOLVENT DENSITY: 7.90 VOC LE: 3.3 VOC AP: 3.3**  
**FLASH POINT: 100°F - 141°F H: 3 F: 2 R: 0 OSHA STORAGE: II**

**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

**4091P(LB)<sup>TM</sup>** Aldehyde resin(21.0%), Barium sulfate(30.3%), Carbon black(16.5%), Dipropylene glycol methyl ether(28.5%), Ethylbenzene(0.8%\* @), Hydrous magnesium silicate(1.2%)

**GAL WT: 12.06 WT PCT SOLIDS: 69.00 VOL PCT SOLIDS: 52.38**

**SOLVENT DENSITY: 7.85 VOC LE: 3.7 VOC AP: 3.7**

**FLASH POINT: 100°F - 141°F H: 1 F: 2 R: 0 OSHA STORAGE: II**

**TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: NO**

Footnotes:

TSCA: in compliance = In compliance with TSCA Inventory requirements for commercial purposes.

ACGIH = American Conference of Government Industrial Hygienists.

IARC = International agency for Research on Cancer.

NTP = National Toxicology Program.

OSHA = Occupational Safety and Health Administration.

PNOR = Particles Not Otherwise Regulated.

PNOC = Particles Not Otherwise Classified.

STEL = Short Term Exposure Limit.

TWA = Time Weighted Average.

TM = Is a Trademark of E.I. du Pont de Nemours & Co.

\* = Section 313 Supplier Notification: These chemicals are subject to the reporting requirements of Section 313 of the Emergency planning and Right-to-Know act of 1986 and of 40 CFR 372.

@ = Clean Air Act Hazardous Air Pollutant.

# = EPCRA Section 302 - Extremely Hazardous Substance.

NOTICE:

The information on this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Product Manager - Refinish Sales

Prepared by: HazCom Coordinator